



WINDY 286 RL - Manual installation




WINDY 286 RL



WINDY 286 RL

- Quickly fitted to the side panel of a tipper truck thanks to two ergonomic handles.
- Powered by a 5.8 hp HONDA internal combustion engine. 3-year engine warranty.
- Big diameter turbine for more air flow. Turbine casing 5-year WARRANTY.
- Quick turbine stop for greater safety.
- Eccentric rotor to avoid blockages in the axis, with 4 removable blades in 300 HB.
- 5 m suction hose, Ø 160 or 200 mm, with aluminium handle and earth wheel.
- Adjustable cap at the end of the chute to fill the skip evenly.
- No maintenance for the bearing: already lubricated for life.
- Discover in option the CASING KIT to keep all the collected waste in your tipper.



Technical characteristics

MODEL	WINDY 286 RL
<i>Turbine diameter</i>	305 mm
<i>Rotor diameter</i>	286 mm
<i>Blades number</i>	4 removable blades
<i>Sleeve</i>	5 m, Ø 200 mm
<i>Dimensions (L x W x H)</i>	0,80 x 0,58 x 0,83 m
<i>Weight</i>	60 kg
<i>Coupling</i>	Side panel
<i>Drive Motor power</i>	Petrol heat engine HONDA 4,3 kW / 5,8 HP With rope starter 3-year warranty

		Price	Reference
MODELS			
WINDY 286 RL • 4,3 kW / 5,8 HP HONDA petrol engine (3-year GUARANTEE) - Starter motor - Manual start	Ø 160 mm suction hose	2890.00	73954A
	Ø 200 mm suction hose	2990.00	73953A
OPTIONS			
Tachometer on internal combustion engine (rev counter with hour meter)		207.00	99151A
SPARE PARTS			
Blade - unit		27.50	739211
Sucking sleeve Ø 200 mm - Value for 1 m - Delivered in 5 m or 10 m		100.40	32A131